



460Volt - 4 (qty) #12  
T1 T2 T3 GRND

24V - 19 (qty) #14  
1 3 4 5 6 7 8 Spare  
Spare GRND  
ADD 2 WIRES FOR HARD  
WIRED REVERSING EDGE  
S1S2

- Notes:
1. 460V 3ph 60HZ Supply Required
  2. Motor Rated FLA: 3.17 Amps Each Motor
  3. Enclosure 24"H x 20" W x 8" D
  4. NEMA-4 Rating
  5. Rotary Fused Disconnect
  6. Lockable Fused Disconnect
  7. Wire counts INCLUDE ground conductor.
  8. All conduits and drilling must be in the bottom of the enclosure.

- Notes:
1. 460-Volt, 3-Phase Primary Power
  2. NEMA 4 type Control Panel
  3. Control Panel to be wall mounted
  4. Open, Close, Stop Push buttons on panel face
  5. 22oz. PVC Fabric
  6. Exterior Installation
  7. Steel door guides
  8. One (1) remote Open, Close, Stop Station
  9. Photo-eyes for safety beams
  10. Aluminum horizontal
  11. Door jamb material is Steel
  - 12 All visible steel to be primed painted White

**MAXDOOR LLC,**  
HEADQUARTERS & MAIN OFFICE  
1020 W. 14<sup>th</sup> Mile Road, Clawson MI 48017  
PHONE: 248-658-1900 FAX: 248-658-1901  
**SALES & SYSTEM INFORMATION**  
WWW.MAXDOOR-USA.COM  
EMAIL: Sales@MAXDOOR-USA.COM

NO.	DESCRIPTION	BY	DATE

**CUSTOMER**  
**MAXDOOR HD - 1' X - 1'**  
Face of Wall Mount  
Door # SAMPLE HD-001

DRAWING NO. **sample HD-02**  
AUTOCAD FILE NO. **sample HD DWG02**

SCALE NONE  
DRAWN BY DRW  
DATE  
SHEET 11